

CP-0101 Power Spring for E-Z-GO Gas Golf Cars

- 1) Remove drive belt.
- 2) Remove the driven clutch from the cart (keep retaining washer lock washer and bolt for reinstallation)
- 3) Remove the snap ring from the clutch on the clutch post.
 - a. A press is recommended with 2 bolts about 2 inches apart to compress the clutch to remove the pressure on the snap ring. A vise or a second person will work also.
 - b. A word of warning this clutch is spring loaded. When the snap ring is removed the spring is free to recoil.
 - c. Thread a rope through the center hole and secure around the outer edges to prevent recoil (this is a safety measure)
- 4) Disassemble clutch. It is a good idea to replace the ramp shoes while you have this apart. Ramp shoe part number CP-0031 (4 cycle gas) quantity 3
- 5) Insert new spring
- 6) Reassemble Clutch and install snap ring.
- 7) Install Clutch on cart using existing retaining washer lock washer and bolt.

CP-0101 Power Spring for E-Z-GO Gas Golf Cars

- 8) Remove drive belt.
- 9) Remove the driven clutch from the cart (keep retaining washer lock washer and bolt for reinstallation)
- 10) Remove the snap ring from the clutch on the clutch post.
 - a. A press is recommended with 2 bolts about 2 inches apart to compress the clutch to remove the pressure on the snap ring. A vise or a second person will work also.
 - b. A word of warning this clutch is spring loaded. When the snap ring is removed the spring is free to recoil.
 - c. Thread a rope through the center hole and secure around the outer edges to prevent recoil (this is a safety measure)
- 11) Disassemble clutch. It is a good idea to replace the ramp shoes while you have this apart. Ramp shoe part number CP-0031 (4 cycle gas) quantity 3
- 12) Insert new spring
- 13) Reassemble Clutch and install snap ring.
- 14) Install Clutch on cart using existing retaining washer lock washer and bolt.

